



RECOMMENDED PCB LAYOUT
 RECOMMENDED PCB THICKNESS: 1.6mm
 TOLERANCE: ±0.05 (TOP VIEW)

PART NUMBER
 CTP - 24BA - 6 6 1 X - 0 3 9

SERIES

POSITION & CONTACT
 66 : 6P6C

W: with Flange
 0: without Flange
GOLD FLASH ON CONTACT

- NOTE:**
- MATERIAL:**
 HOUSING: PBT OR PA46 OR PA9T, WITH GLASS FIBER,
 UL 94V-0, STANDARD COLOR-BLACK.
 CONTACTS: PHOSPHOR BRONZE.
 - FINISH:**
 CONTACTS: GOLD PLATED ON CONTACT AREA,
 0.0254µm [1µ"] GOLD PLATED ON SOLDER TAIL,
 WITH ENTIRE CONTACT UNDERPLATED
 1.27µm [50µ"] MIN. NICKEL

TEL:+1 510 4400578 www.Connect-Tech-Products.com		Connect-Tech Products Corp.	
MODULAR JACK SERIES		PCB MOUNT, SIDE ENTRY, FEMALE	
TOLERANCES		ALL PLASTIC, 6P6C	
XX ±0.3	XX ±0.2	DRAWN BY: <i>Q. Q. W.</i>	
X.XXX ±0.1	Angle ±5°	CHECKED BY: <i>Q. Q. W.</i>	
REVISIONS		APPROVED BY: <i>Q. Q. W.</i>	
REV.	DATE	DESCRIPTION	SCALE
A	0815,2005	RELEASE	MM NONE
20001		A4 D024-BA039	