



P.C.B. LAYOUT  
TOP VIEW ±0.05

**MATERIALS**

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK  
TERMINAL: PHOSPHOR BRONZE, GOLD PLATED

**SPECIFICATION**

CURRENT RATING: 0.5 AMP MAX  
DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
CONTACT RESISTANCE: 30m OHMS MAX  
INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V  
OPERATION TEMPERATURE: -25°C~+85°C

**PART NUMBER**

CTP - 40GB - 0 6 1 T - 0 2 9  
SERIES | NUMBER OF POS. | TIN PLATED ON TAIL | GOLD FLASH ON CONTACT

**Connect-Tech Products Corp.**  
TEL: +1 510 4400578 www.Connect-Tech-Products.com

TOLERANCES	MEMORY CARD SERIES
XX ±0.3	SIM CARD, 6PIN
X.XX ±0.2	FEMALE, SMT
X.XXX ±0.1	
Angle ±5°	

REV.	DATE	DESCRIPTION
B	0121.2011	UPDATE PIN SIGNAL
A	0103.2011	RELEASE

DRAWN BY	CHECKED BY	APPROVED BY
9900N	L. Q. W.	Shing
UNIT	SCALE	SIZE
MM	NONE	A4
DRAW NO.	REV.	
D040-GB029	A	